

# **FM** FACILITY maintenance

## **ONE STEP FLOOR MAINTAINER/CLEANER**

An easy-to-use, thermoplastic ultra high speed (UHS) floor finish restorer that combines the finest polymers, surfactants, synthetic waxes, and solvents. This product provides a brilliantly reflective shine. Designed to reduce mop and machine drag. Guaranteed not to attack or yellow floor finish when used as directed.

### **FEATURES**

- ▶ UHS Compatible
- ▶ Detergent Blended
- ▶ Excellent Leveling Ability
- ▶ Soil Resistant
- ▶ Excellent Visual Gloss
- ▶ Minimizes Maintenance Costs
- ▶ Meets or exceeds ASTM slip resistant requirements
- ▶ Concentrated For Economy
- ▶ Outstanding Fresh "User Friendly" Fragrance

**APPLICATIONS** (Dilute 1:3 for Spray Buff; Dilute 1:42 to 1:20 (3-6 oz. per gal.) as a restorer, Dilute 1:42 - 1:64 (2 - 3 oz/ gal. as floor cleaner)

- ▶ Perfect for use in any "quick-fix" assignment that still require the same beautiful results as a complete refinishing session.

### **TARGET MARKETS**

- ▶ Supermarkets
- ▶ Hospitals
- ▶ Nursing Homes
- ▶ Department Stores
- ▶ Office Buildings
- ▶ Airports
- ▶ Hotels/Motels
- ▶ Banks



**D  
A  
I  
L  
Y**



primegroup**FM**solutions

4407 Center Street • Saginaw, MI 48604

810.603.3230

**FC-33**

## DIRECTIONS

## PRODUCT DATA



1. Always dilute properly and utilize proper protective equipment. Dilute 42 oz. with one gallon of cold water for spray buffs, 3-6 oz. per gallon as a restorer or 2-3 oz. per gallon as a cleaner.



2. Apply floor finish restorer to floor surfaces using thin coats and a clean mops with a spray bottle or an auto scrubber. (Product will dry to a dull haze and will restore gloss after burnishing when used as a mop-on restorer.)



3. When using with an auto scrubber, product should be diluted properly in the solution tank. Scrub floor and allow to dry to touch before high-speed burnishing. Product may dry to a dull haze but will restore to a high gloss after burnishing.

Acrylic Fortified  
Slip Resistant (meets ASTM Standards)  
Black Heel Mark Removal  
Black Heel Mark Resistant  
Soil Resistant  
Concentrated  
pH Buffered  
DOT Regulated  
UL Classified

YES	NO
X	
X	
X	
X	
X	
X	
X	
X	
X	X
X	